

American Fiber Cushion

2410 S. Dixie Hwy.

P.O. Box 2084

Dalton, GA 30722-2084

706-217-1900

Fax: 706-217-1904

FORTITUDE SPECIFICATIONS

WEIGHT	20 OZ.	24 OZ.	28 OZ.	32 OZ.	32 OZ. DS	40 OZ.	40 OZ. DS
THICKNESS	0.250	0.275	0.300	0.360	0.325	0.420	0.375
DENSITY lbs./cu. ft.	6.6	7.0	7.7	8.2	10.0	8.9	8.9
TENSILE STRENGTH:							
LENGTH	152	161	285	313	245	340	205
WIDTH	160	215	293	340	290	354	238
PILL TEST	PASS	PASS	PASS	PASS	PASS	PASS	PASS
FHA TYPE/CLASS	N/A	H 1 & 2	H 1 & 2	H 1 & 2	H 1 & 2	H 1 & 2	H 1 & 2
RADIANT PANEL-ASTME 648	CLASS 1	CLASS 1	CLASS 1	CLASS 1	CLASS 1	CLASS 1	CLASS 1
ROLL WIDTH	6'/12'	6'/12'	6'/12'	6'/12'	6'/12'	6'/12'	6'/12'
ROLL LENGTH	60'/60'	60'/60'	60'/60'	60'/60'	60'/60'	60'/60'	60'/60'

WARRANTY:

American Fiber Company, Inc. warrants that its manufactured products are free from any defects in workmanship and material, will provide satisfactory service and a lively and resilient foundation for the life of the carpet under which it is originally installed. This warranty applies only when properly installed over flat, smooth, hard surfaces on or above grade. The synthetic fiber is mold, moth, mildew, and odor resistant and can be used below grade.

American Fiber Company, Inc. as a sole and exclusive remedy, will replace, without charge, any manufactured product which does not render satisfactory service in normal use F.O.B. manufacturing plant. This warranty does not include the cost of removal or installation. No liability will be assumed for any consequential damage, loss, or expense.