

American Fiber Cushion

207 Recycling Way

P.O. Box 2084

Dalton, GA 30720

Ph: 706-217-1900

Fax: 706-217-1904

MATRIX - FIBER /FOAM CARPET PAD SPECIFICATIONS

| | | | |
|---|--------------------|-------------------|-------------------|
| THICKNESS | 3/8" | 7/16" | 1/2" |
| Density lbs/ft3 (oz/yd2): | 5.4 lbs/ft3 | 6.0 lbs/ft3 | 8.0 lbs/ft3 |
| R-Value | 1.46 | 1.66 | 1.87 |
| Sound Transmission Class STC (dB): | | | |
| ASTM E90-04/ASTM E 413-10 | 61 | | |
| Impact Insulation Class IIC (dB): | | | |
| ASTM E 492 – 09 / ASTM E989-06 | 85 | | |
| Increase in Impact Insulation Class DIIC | | | |
| ASTM E 2179 – 03 | 44 | | |
| Pill Test (DOC/CPSC FF 1-70) | PASS | PASS | PASS |
| HUD/FHA UM-72a Class Rating: | H 1 | H 1 & 2 | H 1 & 2 |
| ROLL SIZE : | 6' x 45' (30 yd2) | 6' x 45' (30 yd2) | 6' x 45' (30 yd2) |
| Roll Weight : | 45 lbs. | 58 lbs. | 89 lbs . |
| Warranty: | Life of the Carpet | | |

WARRANTY:

American Fiber Company, Inc. warrants that its manufactured products are free from any defects in workmanship and material, will provide satisfactory service and a lively and resilient foundation for the life of the carpet under which it is originally installed. This warranty applies only when properly installed over flat, smooth, hard surfaces on or above grade. The synthetic fiber/foam is mold, moth, mildew, and odor resistant and can be used below grade.

American Fiber Company, Inc. as a sole and exclusive remedy, will replace, without charge, any manufactured product which does not render satisfactory service in normal use F.O.B. manufacturing plant. This warranty does not include the cost of removal or installation. No liability will be assumed for any consequential damage, loss, or expense.