



P.O. BOX 2084 • 207 RECYCL
DALTON, GA 30720
706.217.1900 • FAX:706.21
TOLL FREE: 855.803.5092

36 OZ ULTRA SPECIFICATIONS

WEIGHT	36 OZ.
THICKNESS	0.330
DENSITY lbs./cu. ft.	9.0
TENSILE STRENGTH:	
LENGTH	215
WIDTH	229
PILL TEST	PASS
FHA TYPE/CLASS	H 1 & 2
RADIANT PANEL-ASTME 648	CLASS 1
TVOC	1.00 MG
BHT	0.30 MG
FORMALDEHYDE	0.05 MG
4-PC	0.05 MG
STT	74
ROLL WIDTH	6'
ROLL LENGTH	60'/60'
ROLL WEIGHT	85 LBS

Manufactured with an attached extruded polypropylene foam product. Contains microban antimicrobial protection.

WARRANTY:

American Fiber Company, Inc. warrants that its manufactured products are free from any defects in workmanship and material, will provide satisfactory service and a lively and resilient foundation for the life of the carpet under which it is originally installed. This warranty applies only when properly installed over flat, smooth, hard surfaces on or above grade. The synthetic fiber is mold, moth, mildew, and odor resistant and can be used below grade.

American Fiber Company, Inc. as a sole and exclusive remedy, will replace, without charge, any manufactured product which does not render satisfactory service in normal use F.O.B. manufacturing plant. This warranty does not include the cost of removal or installation. No liability will be assumed for any consequential damage, loss, or expense.

ING WAY

7.1904
